MT-32

LS ELECTRIC — Metasol Thermal Overload Relay



GENERAL	
Product code	**1296000100**
Product description	**MT-32 0.14A 2H SCREW EXP (MT32-2H-0.14-S-E)**
Product type	**Metasol Thermal Overload Relay**
Product name	**MT-32/2H**
Heater type	**2H (Non differential 2-heater, Trip class 10A)**
Current range	**0.14(0.1~0.16A)**
Type of terminal	**Screw**
Local/Export	**Export**
Standards	**IEC 60947-4-1, IEC 60947-5-1, UL508**
Certificates	**CE, UL, CCC**
Certificates	**KR, LR, BV, DNV, ABS, NK, RINA**
CHARACTERISTICS	
Poles description	**3P**
Trip class	**10A**
Rated operational voltage [Ue]	**690V**
Rated insulation voltage [Ui]	**690V**
Rated withstand voltage [Uimp]	**6kV**
Rated frequency [Hz]	**50/60Hz**
Temperature compensation (°C)	**-5°C ~ 40°C**
Functions	**Trip indicating**
Functions	**Stop**
Functions	**Test**
Functions	**Manual/Automatic Reset**
Type 2 Coordination with MCCB & TOR (440V)	**See the Type 2 table**
Conductor size (AWG)	**18~8**
Conductor size (mm2)	**6~10**
Conductor charateristic	**65/75°C Cu-wire only**
Main terminal size	**M4**
Torque (lb-in)	**20**
Torque (Nm)	**2.26**
Torque (kgf.cm)	**22.9**
ENVIRONMENT	
Degree of protection	**IP20**
Ambient air temperature	**-30°C ~ +65°C at storage**
Ambient air temperature	**-25°C ~ +60°C at operation**
Mounting position	**Vertical plane**
Shock resistance (1/2 sin wave=11ms)	**15gn - 11ms**
Vibration resistance (Conforming to IEC68-2-6) (5~300Hz)	**6G**

REACH	**Yes**
RoHS	**Yes**
WEEE	**Yes**
DIMENSIONS	
Weight (kg)	**0.17**
Size width	**45mm / 1.85inch**
Size height	**75mm / 3.09inch**
Size depth	**90mm / 3.7inch**
Drawings	**MT-32.png**
AUXILIARY CONTACTS	
Composition	**1NO+1NC**
Rated thermal current	**5A**
Rated operation current	**C600,R300**
Rated operation current	**1.5A at 120V (AC15 duty)**
Rated operation current	**0.75A at 240V (AC15 duty)**
Rated operation current	**0.47A at 380V (AC15 duty)**
Rated operation current	**0.375A at 480V (AC15 duty)**
Rated operation current	**0.35A at 500V (AC15 duty)**
Rated operation current	**0.3A at 600V (AC15 duty)**
Rated operation current	**0.22A at 120V (DC13 duty)**
Rated operation current	**0.1A at 240V (DC13 duty)**
Conductor size (AWG)	**18**
Conductor size (mm2)	**1**
Conductor charateristic	**65/75°C Cu-wire only**
CHARACTERISTIC CURVE	
Characteristic Curve	**Class 10A, 40AF.png**